

Magic Lube



MAGIC LUBE®

Twice the PTFE

MAGIC LUBE II®

A Silicone Based Lubricant/Sealant Formulated For Use Under The Most Adverse Conditions

MAGIC LUBE GREEN®

A PTFE based lubricant/sealant formulated with Aramid Fibers For use as an all purpose pool & spa lube.

Magic Lube®

A Better Solution

Our Magic Line began almost by accident. After receiving a growing number of complaints concerning leaking gaskets and o-rings, we launched an intensive research program to discover the cause. We found that, in many situations, the leaking was due to corrosion caused by the use of petroleum based lubricants.

It is surprising how many people are not aware that petroleum based products corrode rubber. This can be a real problem because many of the most popular lubricants on the market are petroleum based. It was obvious that a solution was needed.

It has long been a tradition at Aladdin to provide positive solutions to our customer's problems. With that in mind, we set out to develop a very special line of lubricants and sealants capable of withstanding the unusual demands of pool and spa applications.

The result... Magic Lube® and Magic Lube II®... exceptional products for lubricating and sealing! They've been formulated to be corrosion free on many materials including rubber... even in the most adverse conditions such as salt water. Safety is also an important factor so, our formulas had to be very special... for your safety and for the safety of the environment! Magic Lube® and Magic Lube II® have received an environmental safety rating of H-1 by the USDA.

“The Only USDA H-1 Rated Lubes”

MAGIC LUBE®

Magic Lube® is a PTFE based, multipurpose sealant/lubricant that can be used in both wet and dry environments with a temperature range of -10° to 425°F. It forms a durable, adhesive film that prevents contact, even under severe shock loads. Specially formulated to be non-melting, non-volatile, and waterproof, Magic Lube® has been USDA H-1 rated to be environmentally safe. It is chemical resistant and compatible with most metals, rubbers and plastics. It is commonly used on motors, o-rings, gaskets, bearings, waterfilters and much more.

- NS0050** Pillow Pack 3 grams
- No. 630** Display Box (25 - 1oz. Tubes)
Master Carton 10 Display boxes (250 - 1oz. Tubes)
- No. 631** 5oz. Tube
Master Carton 50 - 5oz. Tubes
- No. 653** 1Gallon (7 lbs.)
- No. 654** 5 Gallons (35 lbs.)
- No. 655** 55 Gallons (400 lbs.)



No.650

No.630

USDA H-1 Rated

NEW MAGIC LUBE II®

An extraordinary silicone based lubricant and sealer formulated for use under the most adverse conditions. This extremely durable synthetic compound is non-melting and ideal for valves and other special applications that require the added protection and lubrication of silicone. Magic Lube® II has been USDA H-1 rated to be environmentally safe and is completely waterproof and chemical resistant.

- NS0043** Pillow Pack 3 gram
- No. 650** Display Box (25 - 1oz. Tubes)
Master Carton 10 Display Boxes (250 - 1oz. Tubes)
- No. 651** 5 oz. Tube
Master Carton 50 - 5 oz. Tubes
- No. 656** 1 Gallon (8 lbs.)
- No. 657** 5 Gallons (40 lbs.)
- No. 658** 55 Gallons (440 lbs.)

USDA H-1 Rated

MAGIC LUBE GREEN®

Magic Lube Green® has been specially formulated to do the job of an all-purpose Pool and Spa lubricant/sealant providing optimum sealing and lubrication properties. Aramid fiber provides enhanced sealing properties by a mechanism called "Bridging". During make-up, the Aramid fibers intertwine to help hold the PTFE particles in place. The webbing produced also guards against connection seizure by reducing the potential for metal-to-metal contact. The webbing also has the ability of self-healing any small leaks that may develop by entrapping other sealing particles. The bridging or webbing properties accelerates the "damaging" in the helical void in engaged threads. In layman's terms this means MAGIC LUBE GREEN® stays on the o-ring longer, providing greater protection.

- No. 640** 3oz. Display Tube (with hanger hole)
Master Carton (50 - 3oz. Tubes)