

BE A 24VDC ACTUATED IN-GROUND POOL OR SPA LIFT.

ALL METAL COMPONENTS SHALL BE MADE FROM TYPE 304 STAINLESS STEEL. FOR ADDED CORROSION PROTECTION, ALL METAL PARTS SHALL BE EPOXY-POWDER-COATED. THE LIFT SHALL HAVE A DYNAMIC LIFTING CAPACITY OF 350 LBS* [159 kg]. THE SCOUT POOL LIFT SHALL HAVE A RANGE OF 46" [117cm]. THE SCOUT POOL LIFT SHALL FIT INTO A STANDARD ϕ 1.9" X 6" DEEP ANCHOR. IT SHALL HAVE A SELF-LOCKING BASE TO PREVENT ROTATION. IT SHALL COME STANDARD WITH AN 18" [45.7 cm] WIDE SEAT, AND SHALL BE CAPABLE OF BEING FULLY SELF-OPERABLE. IT SHALL ALSO COME WITH A SAFETY BELT, ADJUSTABLE FOOTREST AND DUAL FLIP-UP ARMRESTS. A LIMITED LIFETIME WARRANTY IS STANDARD.

THE SCOUT LIFT IS AVAILABLE WITH AN ANCHOR [F-800SC] OR WITHOUT [F-802SCNA]. *THE LIFTING CAPACITY IS 300 LBS [136 kg] IF USED WITH PLASTIC-SLEEVE 1.9" ANCHOR.



9889 GARRYMORE LANE MISSOULA, MT 59808 (406) 549-0769 FAX (406) 549-2602

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

PRODUCT: F-800SC		
DWG#: F-800SC-1		
SCALE:	1:24	DATE: 7/27/11
DRAWN BY:	DS	REVISION: C