

# FULLFLOXF<sup>®</sup> DIVERTER & CHECK VALVES 2-1/2 IN. & 3 IN. 2-WAY, 3-WAY AND CHECK

## Featured Highlights

- Valves available in CPVC for maximum heat resistance
- Maintenance-free PTFE coated diverter seal
- Optimum positive-seal
- Maximum Flow Rate, low head loss
- Chemical-resistant
- Used for diverting, shut-off or mixing applications
- Accepts 2-1/2 in. and 3 in. PVC plumbing
- Field-adjustable stop positions
- Plumbed with inlet at any port
- Designed to work with most industry standard actuators



263059



263060



263056/263057



263068



263077

## Ordering Information

Product	Description	Carton Qty	Carton Wt (Lbs)
<b>2-WAY AND 3-WAY DIVERTER VALVES</b>			
263056	3-Way CPVC 2.5 in. (3 in. slip outside)	1	
263057	3-Way Solar Valve w/ drain-down, CPVC 2.5 in. (3 in. slip outside)	1	
263059	2-Way CPVC 2.5 in. (3 in. slip outside)	1	
263068	90 degree 2-way CPVC 2.5 in. (3 in. slip outside)	1	
<b>2-WAY AND 90 DEGREE CHECK VALVES</b>			
263060	Check Valve CPVC 2.5 in. (3 in. slip outside)	1	
263077	90 degree Check Valve CPVC 2.5 in. (3 in. slip outside)	1	
270119Z	Check Valve Rebuild Kit		