

# System:2™ Mod Media™ Filters — PLM Series by Sta-Rite®



## Greater dirt-loading capacity reduces maintenance

The System:2™ Mod Media™ filter is ideal for small inground and aboveground pools. This filter is a compact adaptation of patented System: 3 technology from Sta-Rite®, so it handles dirt loads up to 15 times greater than sand filters of equivalent size. The result: you capture more dirt between cleanings and minimize time on maintenance.

- Balanced-flow tank design works in unison with the high capacity filter module to collect dirt over its entire surface—holds more dirt so you clean less often.
- Less frequent cleaning also increases filter module service life and lowers lifetime costs.
- Rugged composite construction resists corrosion and weathering.
- Compact design fits easily in tight installations and can be easily shielded from view.



# System:2™ Mod Media™ Filters — PLM Series



Top-mounted pressure gauge and information panels are positioned for easy reading.

Split tank design permits simple, thorough rinse-in-place cleaning to save time.

Posi-Ring® closure is safe, easy to secure, lasts for years.

Balanced-flow tank hydraulics direct water through each side of the filter module for uniform dirt loading to prevent clogging and maximize filtration effectiveness.



## Easy to clean — just spray and go



The Mod Media™ filter contains a one-piece module that simply drops into an easily accessible tank. When cleaning is necessary, just remove the lid (no tools are necessary) and spray-rinse the module while it is still in place.\* It only takes minutes to thoroughly clean the filter and get back into service — fast.



### Less maintenance ...YES!

The balanced-flow tank design directs water through both sides of the filter module which increases dirt-loading without clogging. Holding more dirt means a longer time between cleanings.

\*Modules used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions.

## System Performance

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Optimal† Flow Rate (GPM)
PLM100	48,000	100	50-75
PLM125	60,000	125	50-94
PLM150	72,000	150	50-113
PLM175	72,000	175	50-120
PLM200	72,000	200	50-120
PLM300	72,000	300	50-120

† Operating at this GPM will provide the longest filter cycles combined with the best and greatest dirt-loading capacity. Larger filter area will provide longer filter cycles between cleanings.

**Operating Limits** — Maximum continual operating pressure is 50 PSI. For Pool/Spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C).

One-year limited warranty. See warranty for details.

## Available from:



**Simply Smarter.**

[www.staritepool.com](http://www.staritepool.com)

Phone: 800-831-7133 Fax: 800-284-4151



pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / maintenance products